

UNIVERSAL PROTECTION DEVICE



PANEL MOUNTED
DEVICE WITH
SWITCHING OUTPUT

GEWAS 200

Item No. 600279

Alarm and protection device (without sensor) for panel mounting with snap-on mounting for DIN rail mounting

GENERAL:

Versatile alarm and protection device for DIN rail mounting with universal input (screw terminal) for a large number of external sensors. All sensors with a switching threshold <100 kOhm can be connected, e.g. B. water sensors, float switches, level switches, magnetic contacts, etc. In the event of an alarm, a connected device (e.g. pump, machine) can be switched on or off using a potential-free changeover contact. The internal / external reset button must be pressed to delete the alarm.

TECHNICAL SPECIFICATIONS:

Power supply:	220 / 240 V 50 / 60 Hz
Power consumption:	approx. 3 VA
Sensor input:	2-pole screw terminal
Trigger threshold:	Input resistance <100 kOhm (e.g. from NPN normally open contacts, relays, reed contacts, etc.)
Control output:	potential-free changeover contact
Switching capacity:	250 V AC, 10 A (resistive load), max. 2400 VA 150 V DC, 2 A (resistive load), max. 240 W.
Red / Green LED:	LED for status display (green) on board LED for alarm status (red) on board
Attachment:	Universal base for all common DIN EN support rails
Environmental conditions:	-20 .. + 50 °C and 0..80% RH
Dimensions:	49 x 96 x 59 mm (L x W x H)
Scope of delivery:	Device, operating instructions

VARIANTS:**GEWAS 200 KL**

Item No. 600306

Device with screw terminal (2-pole) for connecting an external reset button

GEWAS 200 AL

Item No. 601041

Device with automatic alarm cancellation

ACCESSORIES OR SPARE PARTS:**GWF-1**

Item No. 601712

Water sensor, 2-pole, without connector, 2 m cable

GSS-1

Item No. 606016

Float switch, 2 m cable for electrically non-conductive media (NC or NO function can be selected)

GNS-1

Item No. 602531

Level sensor, Stainless steel, 2-pole, 2 m cable

GWF-2

Item No. 601778

Textile tape water sensor with loose ends for ultrapure water, 2 m cable



ACCESSORIES

**GNS-1-2-KS**

Item No. 602526

Level sensor, 2-pole

GENERAL:

PVC body with 2 stainless steel poles, 2 m PVC cable and 2.5 mm jack plug

VARIANTS:**GNS-1-5-KS**

Item No. 602529

Level sensor, Stainless steel, 2-pole, 5 m cable

GNS-1-10-KS

Item No. 602530

Level sensor, Stainless steel, 2-pole, 10 m cable

**GWF-1S**

Item No. 601706

Pluggable, highly sensitive water sensor

GENERAL:

2 m cable length, with 2.5 mm jack plug; using the GAZ-1 branch connector, several water sensors can be connected at the same time

VARIANTS:**GWF-1S/5m**

Item No. 601708

Pluggable water sensor, 2-pole, with plug, 5 m cable

GWF-1S/10m

Item No. 601710

Pluggable water sensor, 2-pole, with plug, 10 m cable

FOR ULTRAPURE WATER

**VEKA 2**

Item No. 601726

Extension cable for GWF, 2 m

VEKA 5

Item No. 601728

Extension cable for GWF, 5 m

VEKA 10

Item No. 601731

Extension cable for GWF, 10 m

GENERAL:

Connections: 1 x jack plug 2.5 mm, 1 x jack socket 2.5 mm

**GAZ-1**

Item No. 602748

Branch connector

GENERAL:

with 2 x jack socket 2.5 mm and 1 x jack plug 2.5 mm; required for each additional water sensor