

MAGNET MOUNTS



MH-S
 Item No. 475187
 Magnetic table holder with screw clamp, incl. 2 magnetic plates



MH-T
 Item No. 475188
 Magnetic table stand with stand, incl. 2 magnetic plates



MH-W
 Item No. 475189
 Magnet wall mount, self-adhesive, incl. 2 magnetic plates

EQUIPMENT:

MH-MP

Item No. 475190
 Magnetic plate, set of 2, self-adhesive



MOUNTS



GMH 1300
 Item No. 601091
 Magnet holder for hanging up devices GMH 3000 & GMH 5000 with integrated suspension bracket



HD-22-3 with probe

HD-22-3
 Item No. 700040
 Freely positionable laboratory sensor holding arm for sensors Ø12mm



Device not included

G 1000
 Item No. 481885
 Plastic stand with connection option for USB cable, order free 3D print data or use it yourself



GCLIP1000
 Item No. 475820
 Metal belt clip, self-adhesive for G1000 series

PORTABLE THERMAL PRINTER



HD 40.1
 Item No. 700056
 Portable thermal printer which is connected to a PC or to devices of the DeltaOhm series via a serial RS232 input.

TECHNICAL SPECIFICATIONS:

Printing process:	Thermal printing
Resolution:	203 DPI (8 dots / mm)
Print speed:	Up to 90 mm / s (depending on the state of charge of the battery and the ambient conditions)
Dimensions:	53 x 165 x 105 mm (H x W x D)
Material:	ABS
Scope of delivery:	Device, 4x 1.2 V NiMH batteries, SWD-10 power supply unit, operating instructions, 5 rolls of thermal paper

ACCESSORIES:

HD2110-CSNM

Item No. 700041
 Serial connection cable, 8-pole mini-DIN connector to 9-pole sub-D socket for RS232C, for connecting the printer to devices with a mini-DIN connection.

HD 2110-RS

Item No. 700057
 9-pole sub-D socket for M12, for connecting the printer to devices with an M12 connection.

SWD-10

Item No. 700039
 100 - 240 V AC/ 12 V DC-1 A mains charger.

BAT-40-1

Item No. 475817
 NiMH battery 4 x 1.2 V AA with integrated temperature sensor for HD40-1 printer

RCT

Item No. 475423
 Spare paper
 The set includes 4 rolls of thermal paper with a width of 57 mm and a diameter of 32 mm

REMOTE ACCESS

**LAN 3200**

Item No. 609253

Gigabit Ethernet to USB converter

GENERAL:

For accessing EASYBus modules, GMH portable instruments with the interface or GDUSB 1000 via a network. 2 USB ports for direct connection of EBW 3, USB 3100N or GDUSB 1000 (up to 15 with USB hub). A USB adapter is included in the scope of delivery for the EBW 1, EBW 64 or EBW 250.

Scope of delivery: LAN 3200, Power supply, USB adapter, manual, driver CD

WLAN 3200

Item No. 610289

WLAN or Gigabit Ethernet to USB converter

GENERAL:

For accessing EASYBus modules, GMH portable instruments with the interface or GDUSB 1000 via a network. With 1 USB port, an EBW 3, USB 3100N or GDUSB 1000 can be connected directly (up to 15 with USB hub). A USB adapter is included in the scope of delivery for the EBW 1, EBW 64 or EBW 250.

Weight: 118 g

Dimensions: 100 x 100 x 25.5mm (W x D x H)

Scope of delivery: WLAN 3200, power supply unit, USB adapter, manual, CD

POWER SUPPLY

GB-AA

Item No. 610049

Spare battery Mignon (AA) 1.5 V

GB 9 V

Item No. 601115

Replacement battery 9 V, type IEC 6F22

GAK 9 V

Item No. 601118

NiMH battery 9V

AAA battery

Item No. 601121

AAA battery, 1.2V, NiMH, 2 pieces

AAA battery

Item No. 478759

AAA battery, 1.2V, NiMH, 3 pieces

AA BATTERY

Item No. 478760

AA battery, 1.2V, NiMH, 2 pieces

GNG 5/5000

Item No. 602287

Plug power supply for GMH 5XXX series (220/240 V, 50/60 Hz), output voltage 5 V DC / 30 mA, suitable for devices with bayonet socket

GNG 10/3000

Item No. 600273

Plug power supply for GMH 3XXX series (220/240 V, 50/60 Hz), output voltage 10.5 V / 10 mA, suitable for devices with a power supply socket

CONNECTOR AND CABLE

**MINIDIN 4S**

Item No. 601111

Mini-DIN plug, 4-pole with locking for self-assembly, for GMH 3700 Series

AAG2M

Item No. 601112

GMH 3000 analog output cable, Cable length 2 m, with 2 x banana plugs and 3.5 mm jack plugs

AAG 5000

Item No. 603871

GMH 5000 analogue output cable, cable length 1 m, plug: 1 x bayonet socket LTW 4-pole, 1 x loose ends, with wire end ferrules

INTERFACE

**USB 3100 N**

Item No. 601092

Interface converter GMH3xxx <=> PC, USB, for the electrically isolated connection of a GMH 3xxx to the USB interface of your PC. (Converter is supplied from the interface of the PC)

USB 5100

Item No. 601095

Interface converter GMH 5xxx <=> PC, for the galvanically isolated connection of a GMH 5xxx to the USB interface of your PC. (Converter is supplied from the interface of the PC)

USB 5200

Item No. 607177

Interface converter GMH 5xxx <=> PC with analog output (like USB 5100). Analog output can be set on the device.

**GRS 3100**

Item No. 601097

Interface converter GMH3xxx <=> PC, RS232, 9-pole SUB-D, Connection of a GMH 3xxx to the RS232 interface

**GRS 3105**

Item No. 601099

5-way interface converter GMH3xxx <=> PC, RS232, 9-pole SUB-D. Connection of 5 GMH 3xxx to the RS232 interface of your PC (converter is supplied via a permanently connected plug-in power supply). Delivery incl. 9-pole sub extension cable and 5 connection cables VEKA 3105

**VEKA 3105**

Item No. 601101

Spare connection cable, 2 m, GMH 3xxx <=> GRS 3105

USB adapter

Item No. 601109

Adapter for connecting an RS232 interface converter to a USB interface

