Family Datasheet

senseca

ECO 230

Precision Barometer/Altimeter

- Modern and functional housing
- Waterproof (IP65 / IP67)
- High resolution and accuracy for ambient pressure an altitude
- Adjustable sea level correction
- Altimeter function with convenient height adjustment
- Long-life and maintenance-free sensor3-line display / overhead display at the push of a button
- Trend display, can be used as a variometer
- Backlight
- Robust, long battery life
- Hold-function to freeze measured values
- Min/Max-function for minimum and maximum recorded measured values
- Made in Germany



DESCRIPTION

When developing the ECO230 series, the focus was deliberately on the essential functions of the measurement technology - a high-quality sensor is at the center of attention - the heart of the measuring device - in which no savings were made despite the low overall price!

Fast, precise, and high-resolution:

Resolution: 0.1 hPa (mbar) and resolution of the height display derived from the pressure 0.1 m!

Barometer sensors are used in countless applications: examples include vehicles with combustion engines (air pressure as an important parameter for engine control), altimeters (calculation of altitude using barometric altitude formula), navigation systems, smartphones and, of course, in weather stations. But is the absolute pressure displayed, correct?

Thanks to the optional calibration certificates, the barometer can serve as a perfect reference device for checking the actual accuracy of corresponding devices.



Family Datasheet



ECO 230

Precision Barometer/Altimeter

Display

Thanks to the backlight, the three-line LCD display offers ergonomic wide-angle visibility - by day and by night.

The HOLD function enables the display values to be frozen.

Power supply

2 powerful AA batteries, the energy-saving design and the configurable automatic switch-off function ensure long operation.

Configurable LCD backlight for further energy saving options.

TECHNICAL DATA

Measurement specifications

	Barometer	Altimeter	Temperature	
Measuring range	300,0 to 1100,0 hPa (mbar) abs.	-500,0 to 9000,0 m	-20,0 to 50,0 °C /	
		-1640 to 19999 ft	-4,0 to 122,0 °F	
	4,350 to 15,950 PSI abs.			
	225,0 to 825,0 mmHg (Torr) abs.			
Accuracy	Typ.: ± 1 hPa	Typ. ± 1 m rel. (over a short time with const. ambient pressure @ 25°C)	typ. ± 0,5 °C @ 25°C	
	(at T: 0 to 30 °C)			
	max.: ± 0.25 % FSS equals ± 2 hPa			
Measuring frequency	FAST: 10 measurements per second			
	SLO: Ca. 1 measurement per second			
Overload	4000 hPa abs.			
Additional functions	NVLL: Tare-function, respectively comfortable altitude setting			
	AVR: Averaging over 2 s / 5 s / 10 s			
	Only as Altimeter: Variometer display can be shown with ft/h, m/s, m/h.			

General specifications

Display	3-line with battery status indicator, Backlight, protected by shatterproof screen, overhead display at the push of a button	
Power Supply	2 x AA-Alkaline batteries (scope of delivery)	
Power consumption	<1 mA	
Battery life	> 3000 h typ. continuous operation (without backlight)	
Automatic Power-Off	Yes, configurable by the user	
Operating conditions	-20 to +50 °C (recommended 530 °C); 0 95 % r.h. (short-term condensation possible)	
Storage temperature	-20 to 70 °C (without batteries)	
Protection class	IP67	
Dimensions	108 x 54 x 28 mm	
Weight	approx 140g	
Housing	break-proof ABS, polyester (front panel), Metal clip and carrying strap	

ECO 230 2/3 V1 0- 02/2024

Family Datasheet



ECO 230

Precision Barometer/Altimeter

Scope of delivery

- Hand-held measuring device with permanently connected sensor
- 2xAA batteries
- Manual
- Test report

ORDERING CODES

ECO230		
Precision Barome	eter/Altimeter (e	arlier G 1110)
1	Set-Option - -SET -WPD5	Device, batteries, manual, test report Device, batteries, manual, test report, transport case GKK 1002 Device, batteries, manual, test report, transport case GKK 1002, WPD5 factory calibration

Standard Articles

ECO230 Precision barometer / Altimeter

Pressure connection: without

Set-Option: Device only Art.Nr. 486736

ECO230-SET Precision barometer / Altimeter

Pressure connection: without

Set-Option: Measuring device, suitcase GKK 1002 Art.Nr. 487012

ECO230-WPD Precision barometer / Altimeter

Pressure connection: without

Set-Option: Measuring device, suitcase GKK 1002, WPD5 calibration

certificate, not DAkkS accredited Art.Nr. 487015

Accessories

Replacement parts:

GB-AA-2 Replacement batteries 2x AA Art.-Nr. 600704

Further accessories:

G1000-Cover Rubber protection cover, incl. 2 magnets Art.-Nr. 483958
ST-G1000 Protection bag, leather Art.-Nr. 611373
GCLIP1000 Metal belt clip Art.-Nr. 475820
G1000-BASE ECO-Line table base and wall suspension Art.-Nr. 481885
GKK1000 Case Art.-Nr. 611603

For further articles, please visit Senseca website.