

Temperature-Panelmeter T 9648

Pt100 - Pt1000 - Thermocouple

Features

- LED-Display 14.2 mm red
- Measuring input:
Pt100 -100.0 ... 600.0 °C*
Pt1000, -50.0 ... 200.0 °C*
Fe-CuNi(J), 0 ... 800.0 °C*
NiCr-Ni(K), 0 ... 1200 °C
Pt10Rh-Pt(S), 0 ... 1600 °C
*switch off decimal point possible
- 2nd measuring input (only Pt100; Pt1000) for difference temperature, average value etc.
- Max. 4 outputs, SPDT relays or transistor
- Isolated analog output
0/4 ... 20 mA and 0/2 ... 10 V DC
- Front protection IP65



General

The Temperature-Panelmeter T9648 is suitable for measurement of temperatures in connection with RTD sensors Pt100, Pt1000 and thermocouples Fe-CuNi (J), NiCr Ni (K), Pt10Rh-Pt (S). Devices for other temperature sensors are available on request. The measuring input is isolated. The measuring range can be limited in the configuration level. It is identical with the range of the analog output.

Short information

Programming	Parameters are programmed via front-side membrane keypad.
Alarm outputs	Switching performance min. or max., hysteresis, on-delay time and off-delay time are programmable in range from 1 s up to 9 h.
Digital filter	With activated digital filter last 16 measured values will be averaged continuously and the result shown in the display.
Analog output	Proportional to the input signal an isolated analog output signal 0 ... 20 mA/0 ... 10 V DC or 4 ... 20 mA/2 ... 10 V DC can be generated. Output changes automatically from current signal to voltage signal depending on burden.
2nd measuring input*	The device can be offered with a 2nd measuring input Pt100 or Pt1000 at terminal strip B. It is not possible to mix Pt100 or Pt1000 signals. In this way difference temperatures, average value, larger or smaller value can be displayed. Please ask for further information.

*Note: no isolation between input 1 (terminal strip A) and 2nd measuring input

Technical data

Supply power

Supply voltage	: 230 V AC $\pm 10\%$; 115 V AC $\pm 10\%$, 24 V AC $\pm 10\%$ or 24 V DC $\pm 15\%$
Power consumption	: max. 3.5 VA, with analog output 5 VA
Operating temperature	: -10 ... +55 °C
Rated voltage	: 250 V~ acc. VDE 0110 between input/output/supply voltage
	Degree of pollution 2, over-voltage categoric III
Test voltage	: 4 kV=, between input/output/supply voltage
- conformity	: EN55022, EN60555, IEC61000-4-3/4/5/11/13

Input

Pt100 / Pt1000	: -100 ... 600 °C/-50 ... 200 °C
-Accuracy	: Pt100 and Pt1000 < 0.1 % ± 2 Digit, max. 100 Ohm line resistant
Thermocouples	: Fe-CuNi (J) 0 ... 800 °C, NiCr-Ni (K) 0 ... 1200 °C and Pt10Rh-Pt (S) 0 ... 1600 °C reference junction compensation inserted.
-Accuracy	: < 0.1 % ± 2 digit with compensating cable
Temperature coefficient	: 0.004

Display

Display range	: $\pm 9999(0)$ digit , leading zero suppression.
Parameter display	: LED 2-digit red, 7 mm (parameter - and output indicator)




Output

Relay	: SPDT < 250 V AC < 250 VA < 2 A, < 300 V DC < 50 W < 2 A
Transistor	: max. 3.5 V AC/DC max. 100mA, short circuit protected
Analog output	: 0/4 ... 20 mA burden \leq 500 Ω ; 0/2 ... 10 V burden $>$ 500 Ω , isolated Automatic output changing (burden dependent)
-Accuracy	: 0.1%; TK 0.01%/K

Panel case


Dimensions	: DIN 96x48 mm, material PA6-GF; UL94V-0
Weight	: Front 96x48 mm, mounting depth 100 mm
Electrical connection	: Clamp terminals, 2 mm ² single wire, 1.5 mm ² flexible wire, AWG14
Protection	: Front IP65, terminals IP20, fingersafe acc. German BGV A3

Dimensions




Connection diagrams


Terminal strip A (varies with versions)




Terminal strip B (varies with version)



Terminal strip C (varies with version)



Terminal strip D supply voltage (varies with version)



Controls and indicators



Description


Operation of the device is arranged in 2 levels. While programming, pressing the button saves the current parameter and moves to the next programming step. For selection within a parameter or for entering data, use buttons and .

After powering up, the device is located in the **Working level**. Set points of the alarm outputs can be preselected if available.

Pressing the button for more than 2 seconds, activates the **Configuration level**. Now all the parameters which defines the function of the panelmeter can be programmed.

After finishing the configuration or when no button was pushed for more than 2 minutes, the program returns to the working level. Leaving the configuration level is possible at any time by pressing the button for more than 2 seconds.

Parameter display as status indicator for the alarm outputs A1-A4.



Error codes:

Display flashes Overflow of the display range

Error 1 EEPROM test. Reading this message, a program error has been occurred. When pushing the button a copy of the EEPROM will be reloaded and the device will work with the factory settings. If this copy does not work, please ship the panelmeter to factory for repair service.

Loc Programming lock active (see configuration page 7)

Start-up note:

Before setting into operation, the device must be configured for the intended use.

⇒ see page 6

Notes to representation



Parameter is only displayed when configurated



Parameter is only displayed when feature is included (see order code)

Please Note: All parameters can be called if they are not blocked by other programmed parameters and if they are available.

Working level

Button	Display	Description
--------	---------	-------------



Actual value.



Alarm output indication
(only if installed and activated).



Display brightness (permanent changing possible)
Setting possible in 9 steps with buttons and .



Display maximum reading.
Reset with buttons or , or at every power off.



Display minimum reading.
Reset with buttons or , or at every power off.



Setpoint output A1.
Setting possible from $5 \text{ t} \dots E n$ with buttons and .
 5 t (start value) ... $E n$ (end value)



Note:
Set points for alarm outputs A2 - A4 have to be configured in the same way.

Configuration

Button	Display	Description (Display graphic shows factory settings)
	1 	Digitalfilter OFF, ON Averaging of the last 16 measured values continuously. Selection with buttons and .
	2 	Input signal selection (only Thermocouple) FeCuNi, NiCrNi, PtRhPt In Selection with button and .
	3 	Decimal point position (not with NiCr.Ni and PtRh.Pt) .0 0. dP Selection with button and .
	4 	Unit of the temperature °C °F Selection with button and .
	5 	Start value for indicating range and analog output Setting possible from min ... En with buttons and min: Pt100 = -100; Pt1000 = -50 °C Fe-CuNi, NiCr-Ni, Pt10Rh-Pt = 0 °C In case of modification a new configuration of the alarm outputs is necessary.
	6 	End value for indicating range and analog output Setting possible from St ... max with buttons and max: Pt100 = 600 °C; Pt1000 = 200 °C Fe-CuNi = 800 °C, NiCr-Ni = 1200 °C, Pt10Rh-Pt = 1600 °C In case of modification a new configuration of the alarm outputs is necessary.
	7 	Display correction Setting possible from -99 ... 99 Digit with buttons and .

continue
page 7

Button	Display	Description (Display graphic shows factory settings)						
↓	8 R I	Switching performance output A1. Function <i>oFF</i> ; <i>on</i> (min); or <i>on</i> (max). If activated the start value will be loaded for set point. Selection with buttons and .						
↓	9 R I	Set point output A1. Setting possible from <i>S t</i> (start value) ... <i>E n</i> (end value) with buttons and .						
↓	10 H I	Hysteresis A1 Setting possible from <i>t</i> ... <i>9999</i> digit with buttons and .						
↓	11 E I	Switch-on delay time output A1. Setting possible from <i>0.00.00</i> ... <i>9.00.00</i> (h.mm.ss) with buttons and .						
↓	12 E I	Switch-off delay time output A1. Setting possible from <i>0.00.00</i> ... <i>9.00.00</i> (h.mm.ss) with buttons and .						
↓	13 R o	Note: Switching performance and set points for alarm output A2 ... A4 has to be configured in the same way.						
↓	13 R o	Analog output. <i>0 - 20</i> mA (0 - 10 V DC) or <i>4 - 20</i> mA (2 - 10 V DC). Changing from current to voltage output is load-dependent (≤ 500 Ω = current output, > 500 Ω = voltage output). Selection with buttons and .						
↓	14 E o	Code for factory settings.						
↓	15 L c R L L	Programming lock. <table> <tr> <td><i>oFF</i></td> <td>= no lock</td> </tr> <tr> <td><i>CoN F</i></td> <td>= configuration level locked</td> </tr> <tr> <td><i>R LL</i></td> <td>= all parameters locked</td> </tr> </table> Selection with buttons and .	<i>oFF</i>	= no lock	<i>CoN F</i>	= configuration level locked	<i>R LL</i>	= all parameters locked
<i>oFF</i>	= no lock							
<i>CoN F</i>	= configuration level locked							
<i>R LL</i>	= all parameters locked							
↓	16 	Return to the working level						

Ordering code

T9648 - - - - - - -

1. Terminal strip A

1	Input Pt100	-100.0 ... 600.0 °C
3	Input Pt1000	-50.0 ... 200.0 °C
5	Input thermocouple Fe-CuNi (J) NiCr-Ni (K) Pt10RH-Pt (S)	0 ... 800.0 °C 0 ... 1200 °C 0 ... 1600 °C

2. Terminal strip B

00	not installed	
2R	2 alarm outputs	Relay
2T	2 alarm outputs	Transistor
T1*	2 nd input Pt100	-100.0 ... 600.0 °C
T3*	2 nd input Pt1000	-50.0 ... 200.0 °C

3. Terminal strip C

00	not installed	
2R	2 alarm outputs	Relay
2T	2 alarm outputs	Transistor
AO	analog output	0/4 ... 20 mA or 0/2 ... 10 V DC isolated

4. Terminal strip D supply voltage

0	230 V AC	± 10 %	50-60 Hz
1	115 V AC	± 10 %	50-60 Hz
4	24 V AC	± 10 %	50-60 Hz
5	24 V DC	± 15 %	

5. Options

00	without option	
01	Min- und Max-value hold	
02	Difference-, average value, larger value, smaller value	
07	Display brightness programmable	

6. Unit (appears in the unit field)

7. Additional text (appears in the field for additional text
max. 3 x 90 mm, WxH)

Attention:

* in connection with terminal strip A, only Pt100 or Pt1000 are available
(Pt100 and Pt1000 cannot be mixed).

Note: not isolated to terminal strip A.