

# Lufft WS700-UMB – Temperature, Relative Humidity, Precipitation, Solar Radiation, Air Pressure, Wind, Electronic Compass

From the WS product family of professional intelligent measurement transducers with digital interface for environmental applications.

Integrated design with ventilated radiation protection for measuring:

- Air temperature
- Relative humidity
- Precipitation intensity
- Precipitation type
- Precipitation quantity
- Air pressure
- Wind direction
- Wind speed
- Solar radiation

Relative humidity is measured by means of a capacitive sensor element; a precision NTC measuring element is used to measure air temperature.

Ultrasonic sensor technology is used to take wind measurements.

Measurement output can be accessed by the following protocols:  
UMB-Binary, UMB-ASCII, SDI-12, MODBUS

**One external temperature or rain sensor is connectable.**

Lufft WS700-UMB Smart Weather Sensor			Order No.
<b>WS700-UMB</b>			<b>8380.U01</b>
<b>Technical Data</b>	Dimensions	Ø approx. 150mm, height 317mm	
	Weight	Approx. 1.5kg	
<b>Temperature</b>	Principle	NTC	
	Measuring range	-50 ... 60 °C	
	Accuracy	± 0.2 °C (-20 °C ... +50 °C), otherwise ± 0.5 °C (>-30 °C)	
<b>Relative humidity</b>	Principle	Capacitive	
	Measuring range	0 ... 100 % RH	
	Accuracy	± 2 % RH	
<b>Precipitation quantity</b>	Resolution	0.01 mm	
	Measuring range	Drop size 0.3 ... 5 mm	
	Reproducibility	typ. > 90 %	
<b>Precipitation type</b>	Rain/snow		
<b>Radiation</b>	Response time (95%)	< 1s	
	Spectral range	300 to 1100 nm	
	Measuring range	1400 W/m <sup>2</sup>	
<b>Air pressure</b>	Principle	MEMS capacitive	
	Measuring range	300 ... 1200 hPa	
	Accuracy	± 0.5 hPa (0...+40°C)	
<b>Wind direction</b>	Principle	Ultrasonic	
	Measuring range	0 ... 359.9°	
	Accuracy	< 3° RMSE >1.0 m/s	
<b>Wind speed</b>	Principle	Ultrasonic	
	Measuring range	0 ... 75 m/s	
	Accuracy	± 0.3 m/s or 3 % (0 ... 35 m/s) RMS of reading, whichever is greater ± 5 % (>35 m/s) RMS	
<b>General Information</b>	Heating	20VA at 24VDC	
	Protection type housing	IP66	
	Interface	RS485, 2-wire, half-duplex	
	Operating voltage	4...32 VDC	
	Operating humidity range	0 ... 100 %	
	Operating temperature range	-50 ... 60 °C	
<b>Accessories</b>	Surge protection		<b>8379.USP</b>
	Power supply 24V/4A		<b>8366.USV1</b>
	UMB Interface converter ISOCON-UMB		<b>8160.UISO</b>
	Digital-analog-converter DACON8-UMB		<b>8160.UDAC</b>
	Temperature Sensor WT1		<b>8160.WT1</b>
	Connection cable, 20m		<b>8370.UKAB20</b>



All in One  
Aspirated temperature/humidity measurement  
Open communication protocol:  
- UMB-ASCII  
- UMB-Binary  
- SDI-12  
- MODBUS  
- Analogue outputs in combination with 8160.UDAC