

24513 COMBINED NAVAL WIND SENSOR



Modern electronics...

paired with robust mechanics. Mechanical abrasion is reduced to a minimum. The measured wind values are serially supplied at every second as a NMEA protocol. Under extreme weather conditions at sea, as well as on land, this top sensor is the first choice!

- seawater resistant housing
- IP 65
- low starting values
- high measuring accuracy and linearity across the whole measuring range
- NMEA 0183
- high quality and durable construction

APPLICATIONS

- professional marine meteorology
- coastal surveillance
- off shore wind power plants
- drilling platforms
- buoys
- aggressive environmental conditions

Professional Line	24513 Combined naval wind sensor
Id-No.	00.24513.205010
Meas. range wind direction	0...360°
Meas. range wind speed	0.4...60 m/s
Accuracy wind direction	± 2.5°
Accuracy wind speed	± 2 % FS
Resolution wind direction	< 1°
Resolution wind speed	0.1 m/s

Continued on page 2

Professional Line		24513 Combined naval wind sensor
Starting value		wind direction: < 0.8 m/s related to a deflection of the wind vane of 90° • wind speed: ≤ 0.4 m/s
Protocols		NMEA 0183 • WIMWV
Interface		serial RS 485/ Talker baud rate 4800 • 1 Hz (at measuring cycle 4 Hz) • 8 N 1
Range of application		temperatures -35...+70 °C heated • wind speed 0...60 m/s
Supply voltage		24 VDC/ 50 mA • heating 24 VDC/ 1.5 A/ max. 35 VA • electr. controlled
Measuring elements		wind direction: wedge-shaped wind vane • wind speed: 3-armed cup rotor
Dimensions		cup rotor Ø 280 mm • H 520 mm • for mounting pipe Ø 50 mm
Housing		seawater resistant aluminium
Weight		2.7 kg
Options (order separately)		Data logger met[LOG] • Visualisation and evaluation software MeteoWare-CS3 • Display unit METEO-LCD/NAV
Accessories (order separately)		32.16420.066100 Sensorkabel, 10 m • 12-pole bayonet plug

As of: 11.06.2019