

# Vantage Pro2 Sensors

## anemometer



**SENSORS**

### Vantage Pro2 Sensors Anemometer

art.no. 6410

Anemometer with sensors for wind speed and wind direction (console Vantage Pro2, Vantage Vue or Weather Envoy are requested).

scope of delivery:

- anemometer with sensors for wind speed and wind direction
- 12 m cable

<b>wind speed</b>	meas. range:	1.0 m/s to 80.0 m/s or 1 km/h to 320 km/h
	resolution:	0.1 m/s or 1 km/h
	accuracy:	±5 %
	wind speed can optionally be indicated in meters/second (m/s), kilometers/hour (km/h), miles/hour (mph) or knots	
	wind development in connection with WeatherLink only	
<b>wind direction</b>	meas. range:	0° to 360°
	resolution:	1° on numeric display, 22.5° on compass rose
	accuracy:	±3°
<b>general information</b>	sensor:	solid state magnetic sensor (wind speed); wind vane and potentiometer (wind direction)
	dimensions (L x W x D):	381 mm x 457 mm x 38 mm
	weight:	approx. 1.33 kg
	material:	UV-resistant ABS (wind vane and control head); polycarbonate (wind cups); black-anodized aluminum (anemometer arm)
	cable type:	4-conductor, 26 AWG
	connectors:	modular RJ-11
	attached cable length:	12 m
recommended maximum cable length:	73 m	

Order directly online at: [www.gsg-e-shop.com](http://www.gsg-e-shop.com)